

# ISUZU DIESEL

IRRIGATION POWER UNITS							
		GEAR RATIO	1:1	11:10	6:5	5:4	MAX RPM
		ENGINE RPM	1760	1936	2112	2200	MAX HP
MODEL	Displacment	No. Cyl.					
3LB1	68.6 1.12L	3	14	16	17	18	3000 25
3LD1	91.3 1.5L	3	19	20	21	23	3000 33
3CD1	91.8 1.5L	3	23	25	26	27	3000 33
3CD1T	91.8 1.5L	3 Turbo	29	30	33	34	2800 39
4LE2	133 2.2L	4	33	40	42	44	3000 52.4
4JG1T	190 3.1L	4 Turbo	52	60	64	67	2500 83
4BG1	264 4.3L	4	60	63	66	67	2500 89
4BG1T	264 4.3L	4 Turbo	80	85	90	92	2500 111
6BG1	396 6.5L	6	85	90	95	97	2500 129
6BG1T	396 6.5L	6 Turbo	132	140	146	148	2500 174
6BG1T-II	396 6.5L	6 Turbo	125	143	156	158	2200 174
6BG1TC	396 6.5L	6 Turbo/cac	145	160	170	171	2200 191
6HK1T	475 7.8L	6 Turbo	175	182	N/A	N/A	2000 182
6SD1T	598 9.8L	6 Turbo	190	200	210	212	2500 212
6HK1TC	475 7.8L	6 Turbo/cac	233	246	N/A	N/A	2000 247
6SD1TC	598 9.0L	6 Turbo/cac	300	305	N/A	N/A	2000 306
6WG1T	956 15.7L	6 Turbo	315	N/A	N/A	N/A	1800 315
6WG1TC	956 15.7L	6 Turbo/cac	440	N/A	N/A	N/A	1800 453

Recommended Application at 2500' Elevation and 100 deg F. Less Fan and Radiator