

8.8 Liter

Energy

PRODUCT SPECIFICATIO	NS				
Model Number	8.8L				
Cylinders	V-8				
Combustion System	Spark-ignited				
Cooling System	Water-cooled				
Displacement	535 cid (8,799.9 cc)				
Compression Ratio	10:1				
Bore & Stroke	4.35 in x 4.50 in (110.5 mm x 114.3 mm)				
Fuel Type	NATURAL GAS (NG), PROPANE (LP)				
Direction of rotation	Counter-clockwise viewed on flywheel				

SAE J1995 rated following 56100020 PSI Derate Specification with a tolerance of +/-5%. Power and torque values are based on standard assumptions. kWe values are based on standard assumptions for mechanical and electrical losses. Ratings and performance are solely for reference only and subject to site conditions and PSI application and ratings guidelines. The product images shown are for illustration purposes only and may not be an exact representation of the final product. All information is subject to change without notice.

REQUEST INFO



POWER RATINGS

GENERAL DATA & FEATURES

DIMENSIONS

50 HZ (1500 RPM)					
Rating	Fuel	kWe	kWm	bHp	
Standby	NG	85	101	135	
Standby – T	NG	100	122	164	
Standby - TCAC	NG	125	162	217	
Standby - TCAC	LP	130	172	230	
Standby	LP	110	143	192	
Prime	NG	75	91	122	
Prime	LP	85	103	139	

60 HZ (1800 RPM)				
Rating	Fuel	kWe	kWm	bHp
Standby	NG	100	121	162
Standby - T	NG	125	147	197
Standby - TCAC	NG	150	195	261
Standby - TCAC	LP	130	172	230
Standby	LP	115	138	185
Prime	NG	80	109	146
Prime	LP	100	124	166