



10 Liter

Energy

PRODUCT SPECIFICATIONS	
Model Number	10L
Cylinders	I-6
Combustion System	Spark-ignited
Cooling System	Water-cooled
Displacement	593 cid (11,051 cc)
Compression Ratio	9.75:1
Bore & Stroke	5.00 in x 5.10 in (126 mm x 130 mm)
Fuel Type	NATURAL GAS (NG), PROPANE (LP)
Direction of rotation	Counter-clockwise viewed on flywheel

SAE J1995 rated following 56100020 PSI Derate Specification with a tolerance of +/-5%. Power and torque values are based on standard assumptions. kWe values are based on standard assumptions for mechanical and electrical losses. Ratings and performance are solely for reference only and subject to site conditions and PSI application and ratings guidelines. The product images shown are for illustration purposes only and may not be an exact representation of the final product. All information is subject to change without notice.

[REQUEST INFO](#)



POWER RATINGS

GENERAL DATA & FEATURES

DIMENSIONS

50 HZ (1500 RPM)				
Rating	Fuel	kWe	kWm	bHp
Standby	NG	200	230	284
Standby	LP	135	160	217
Prime	NG	180	200	284
Prime	LP	135	160	217

60 HZ (1800 RPM)				
Rating	Fuel	kWe	kWm	bHp
Standby	NG	204	236	268
Standby	LP	140	168	225
Prime	NG	170	200	268
Prime	LP	140	168	225