



17 Liter

Energy

PRODUCT SPECIFICATIONS

Model Number	17L
Cylinders	V-8
Combustion System	Spark-ignited
Cooling System	Water-cooled
Displacement	1020 cid (16,720 cc)
Compression Ratio	10.5:1
Bore & Stroke	5.00 in x 6.50 in (127 mm x 165 mm)
Fuel Type	NATURAL GAS (NG), PROPANE (LP)
Direction of rotation	Counter-clockwise viewed on flywheel

SAE J1995 rated following 56100020 PSI Derate Specification with a tolerance of +/-5%. Power and torque values are based on standard assumptions. kWe values are based on standard assumptions for mechanical and electrical losses. Ratings and performance are solely for reference only and subject to site conditions and PSI application and ratings guidelines. The product images shown are for illustration purposes only and may not be an exact representation of the final product. All information is subject to change without notice.

[REQUEST INFO](#)

POWER RATINGS

GENERAL DATA & FEATURES

DIMENSIONS

50 HZ (1500 RPM)				
Rating	Fuel	kWe	kWm	bHp
Standby	NG	275	320	—
Prime	LP	275	320	—

60 HZ (1800 RPM)				
Rating	Fuel	kWe	kWm	bHp
Standby	NG	400	460	550
Prime	LP	350	420	550