

# 20 Liter

## Energy



PRODUCT SPECIFICATIONS	
Model Number	20L
Cylinders	I-6
Combustion System	Spark-ignited
Cooling System	Water-cooled
Displacement	1196 cid (19,600 cc)
Compression Ratio	10.5:1
Bore & Stroke	5.90 in x 7.30 in (150 mm x 185 mm)
Fuel Type	NATURAL GAS (NG), PROPANE (LP)
Direction of rotation	Counter-clockwise viewed on flywheel

SAE J1995 rated following 56100020 PSI Derate Specification with a tolerance of +/-5%. Power and torque values are based on standard assumptions. kWe values are based on standard assumptions for mechanical and electrical losses. Ratings and performance are solely for reference only and subject to site conditions and PSI application and ratings guidelines. The product images shown are for illustration purposes only and may not be an exact representation of the final product. All information is subject to change without notice.

[REQUEST INFO](#)

**POWER RATINGS**

GENERAL DATA & FEATURES

DIMENSIONS

50 HZ (1500 RPM)				
Rating	Fuel	kWe	kWm	bHp
Standby	NG	375	425	536
Standby	LP	250	300	536
Prime	NG	350	400	536
Prime	LP	250	300	536

60 HZ (1800 RPM)				
Rating	Fuel	kWe	kWm	bHp
Standby	NG	450	510	603
Standby	LP	250	310	416
Prime	NG	400	450	603
Prime	LP	250	310	416