



# 17 Liter

## Energy

### PRODUCT SPECIFICATIONS

<b>Model Number</b>	17L
<b>Cylinders</b>	V-8
<b>Combustion System</b>	Spark-ignited
<b>Cooling System</b>	Water-cooled
<b>Displacement</b>	1020 cid (16,720 cc)
<b>Compression Ratio</b>	10.5:1
<b>Bore &amp; Stroke</b>	5.00 in x 6.50 in (127 mm x 165 mm)
<b>Fuel Type</b>	NATURAL GAS (NG), PROPANE (LP)
<b>Direction of rotation</b>	Counter-clockwise viewed on flywheel

*SAE J1995 rated following 56100020 PSI Derate Specification with a tolerance of +/-5%. Power and torque values are based on standard assumptions. kWe values are based on standard assumptions for mechanical and electrical losses. Ratings and performance are solely for reference only and subject to site conditions and PSI application and ratings guidelines. The product images shown are for illustration purposes only and may not be an exact representation of the final product. All information is subject to change without notice.*

[REQUEST INFO](#)

### POWER RATINGS

### GENERAL DATA & FEATURES

### DIMENSIONS

50 HZ (1500 RPM)				
Rating	Fuel	kWe	kWm	bHp
Standby	NG	275	320	—
Prime	LP	275	320	—

60 HZ (1800 RPM)				
Rating	Fuel	kWe	kWm	bHp
Standby	NG	400	460	550
Prime	LP	350	420	550