

32 Liter

Energy



PRODUCT SPECIFICATIONS

Model Number	32L
Cylinders	90°, V-12
Combustion System	Spark-ignited
Cooling System	Water-cooled
Displacement	1,941 cid (31,800 cc)
Compression Ratio	10.5:1
Bore & Stroke	5.91 in x 5.91 in (150 mm x 150 mm)
Fuel Type	NATURAL GAS (NG), PROPANE (LP)
Direction of rotation	Counter-clockwise viewed on flywheel

SAE J1995 rated following 56100021 PSI Derate Specification with a tolerance of +/-5%. Power and torque values are based on standard assumptions. kW values are based on standard assumptions for mechanical and electrical losses. Ratings and performance are solely for reference only and subject to site conditions and PSI application and ratings guidelines. The product images shown are for illustration purposes

[COVID-19 Update](#) - [Customers](#) - [Suppliers](#) - [Employees](#)



- [ABOUT](#)
- [SOLUTIONS](#)
- [PRODUCTS](#)
- [CAREERS](#)
- [INVESTORS](#)
- [CONTACT](#)



POWER RATINGS

GENERAL DATA & FEATURES

DIMENSIONS

50 HZ (1500 RPM)				
Rating	Fuel	kWe	kWm	bHp
Standby	NG	525	600	805
Standby	LP	350	405	543
LTP	NG	500	570	738
LTP	LP	325	385	516
Prime	NG	450	510	637
Prime	LP	300	344	461

60 HZ (1800 RPM)				
Rating	Fuel	kWe	kWm	bHp
Standby	NG	650	720	966
Standby	LP	425	475	637
LTP	NG	600	684	918
LTP	LP	400	451	605
Prime	NG	525	600	805
Prime	LP	350	403	540