



53 Liter

Energy

| PRODUCT SPECIFICATIONS | |
|------------------------|--------------------------------------|
| Model Number | 53L |
| Cylinders | 90°, V-16 |
| Combustion System | Spark-ignited |
| Cooling System | Water-cooled |
| Displacement | 3,192 cid (52,308 cc) |
| Compression Ratio | 10.5:1 |
| Bore & Stroke | 5.91 in x 7.28 in (150 mm x 185 mm) |
| Fuel Type | NATURAL GAS (NG), PROPANE (LP) |
| Direction of rotation | Counter-clockwise viewed on flywheel |

SAE J1995 rated following 36300018 PSI Derate Specification with a tolerance of +/-5%. Power and torque values are based on standard assumptions. kWe values are based on standard assumptions for mechanical and electrical losses. Ratings and performance are solely for reference only and subject to site conditions and PSI application and ratings guidelines. The product images shown are for illustration purposes only and may not be an exact representation of the final product. All information is subject to change without notice.

[REQUEST INFO](#)

POWER RATINGS

GENERAL DATA & FEATURES

DIMENSIONS

| 50 Hz (1500 RPM) | | | | |
|------------------|------|-----|-----|------|
| Rating | Fuel | kWe | kWm | bHp |
| Standby | NG | 870 | 986 | 1323 |
| LTP | NG | 825 | 937 | 1257 |
| Prime | NG | 725 | 838 | 1124 |

| 60 Hz (1800 RPM) | | | | |
|------------------|------|------|------|------|
| Rating | Fuel | kWe | kWm | bHp |
| Standby | NG | 1050 | 1200 | 1609 |
| Standby | LP | 696 | 791 | 1061 |
| LTP | NG | 1000 | 1140 | 1529 |
| Prime | NG | 850 | 1020 | 1368 |